

Esse

Una passione costruttiva attenta ad ogni collocazione architettonica: il gusto della tradizione trova espressione nel serramento curvo e nell'attenzione al dettaglio. Le nostre soluzioni su misura trovano collocazione ideale anche nei contesti storici: elementi distintivi perfetti per ogni tipo di ristrutturazione.

Manufactured with passion and perfect for any architectural arrangement: the arched windows and doors embody our endorsement of tradition and our attention to detail. Our customised solutions also look fabulous in historic buildings: perfect sophisticated elements for all renovation purposes.

Esse

Sezione anta 68x78 mm.
Sezione telaio da 68x79 mm, con triplice battuta, a richiesta terza guarnizione; giunzione montante e traverso con parte esterna passante e protezione di eventuali infiltrazioni d'acqua.
Gocciolatoio in alluminio, a richiesta disponibile anche in legno.
Doppia guarnizione in TPE espanso termoacustica montata sul perimetro del battente.
Vetrocamera B. e. 3/3, 18/4 Argon (Ug. 1.10), a richiesta canalina termica Warm-edge; siliconatura interna ed esterna onde evitare il formarsi di condensa e infiltrazioni d'acqua.
Coprifilo complanare ad incastro.

PERMEABILITÀ ARIA
Classe 4 secondo
UNI EN 1026/01 - 12207/00
TENUTA ALL'ACQUA
E900 secondo UNI EN 12208/00 1027/01
RESISTENZA CARICO DEL VENTO
Classe C5 secondo UNI EN 12211/01 12210/00
TRASMITTANZA TERMICA
UW 1.4 secondo UNI EN ISO 10077-2

Window section 68x78 mm.
Frame section 68x79 mm, with triple seal compression, third seal available on request; head and jamb junctions with (pass-through) external component providing a watertight seal. Aluminium rain drip, wooden drip available on request.
Double seal (high-volume thermo-acoustic TPE insulation) along sash perimeter.
Insulated Glazing B. e. 3/3, 18/4 Argon Gas (Ug. 1.10), Warm-edge spacers for thermal insulation are available on request; watertight and anti condensation internal and external silicone sealant.
Snap-in coplanar casing.

AIR TIGHTNESS
Class 4 according to
UNI EN 1026/01 - 12207/00
WATER TIGHTNESS
E900 according to UNI EN 12208/00 1027/01
RESISTANCE TO WIND LOAD
Class C5 according to UNI EN 12211/01 12210/00
THERMAL TRANSMITTANCE
UW 1.4 according to UNI EN ISO 10077-2



Esse



LIVING
WOOD

Via Belgio 7 · z.i. Camin
35127 Padova · Italy
T +39 049 760776

F +39 049 8701663
info@serramenticacco.it
www.serramenticacco.it

Follow us



© 2015 Cacco Serramenti / playsuadigrafico.it



02



ES

